# **Technical Specifications**

149.1 cc

Air Cooled, 4 stroke single cylinder, OHC

10 kW (13.4 BHP)@ 8000 rpm

12.8 N- m@ 5000 rpm

Kick Start / Self Start

ENGINE

Displacement

Compression Ratio

Maximum Torque

TRANSMISSION

Multi- plate, wet type 5- speed constant mesh Gear Box

CHASSIS

Tubular Diamond type

SUSPENSION

Telescopic hydraulic shock absorber Swing Arm with adjustable Shock Absorber

BRAKES

Brakes Front Brakes Rear

Hydraulic Disc type- 240 mm dia, Internal Expanding shoe type - 130 mm dia Internal Expanding shoe type - 130 mm dia

AVAILABLE IN 3 EXCITING COLOURS

Digital-DC CDI Ignition (AMI) Advanced Microprocessor Ignition

TYRES

80/100-18 47P (Tubeless) Tyre Size Rear 80/100-18 54P (Tubeless)

ELECTRICALS

Head Lamps Tail / Stop Lamp 12V- 5Ah (Electric start) (Maintainance free) 12 V - 35W / 35W - Halogen bulb(MFR) 12V- 5W- MFR

DIMENSIONS

Ground Clearance

WEIGHTS

Kerb Weight Max Payload 139 kg 130 kg

2060 mm

763 mm

1290 mm

160 mm

CAPACITY

Fuel Tank Capacity Reserve

13 litre

Fiery Red

#### Hero MotoCorp Ltd.,

Registered Office: 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi – 110057, India.


It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice, Accessories and features shown may not be a part of the standard fitment. Always wear a helmet while riding a two wheeler



al General Marketing Pvt. Ltd.

Toll Free No., NTC: 16600122033, Neall 9801571023

Email: customercare@ngmhero.com, www.ngmhero.com/ngmheromotocorp











Hero Achiever 150 is the first ever bike in its segment with intuitive i3s technology. It automatically switches off the engine when idle for more than 5 seconds and switches it on as soon as you press the clutch. Now ride ahead in style and save fuel on the go.



### Stops when idle

Auto Ignition cut-off when idle for more than seconds



## Restarts instantly

Engine restarts with a press of the clutch



#### Saves fu

Ensures minim consumption of fuel

