AN ALL-NEW RANGE OF EXCITING COLOURS











SPECIFICATIONS

Engine Air-cooled, 4-stroke Single Cylinder OHC

Bore x Stroke 50.0 mm x 52.0 mm

Displacement 102cc Compression Ratio 9.9:1

Maximum Power 5.15 kW (6.9 BHP) @ 7000 Revolutions Per Minute (RPM)

Maximum Torque 8.1 Nm @ 5000 Revolutions Per Minute (RPM)

Maximum Speed 77 km/h

Clutch Dry. Automatic Centrifugal Clutch

Ignition C D Starting Self

Starting Self-start
Front Suspension Bottom Link with Spring-loaded

Hydraulic Damper

Rear Suspension Unit Swing with Spring-loaded Hydraulic Damper

Length x Width x Height 1750 mm x 705 mm x 1115 mm

Wheel Base 1240 mm Ground Clearance 125 mm Kerb Weight 101 kg

Tyres Front 90/100 x 10 - 53 J Rear 90/100 x 10 - 53 J

Front Brake Internal Expanding Shoe Type (130 mm)
Rear Brake Internal Expanding Shoe Type (130 mm)

Internal Expanding Shoe Type (130 mm)
Integrated Braking System (IBS)

5 Litre (Min)

Head Lamp 12 V - 35 W / 35 W - Halogen Bulb

(Multi-Reflector Type) 12 V - 5 W X 2 Nos.

Battery 12 V - 4 Ah MF Type (Maintenance Free)

This product is BS-IV compliant.





Authorised Outlet



Fuel Tank Capacity

Position Lamp

Nepal General Marketing Pvt. Ltd.
PO Box 133, Jyoti Bhawan 1911, Kantipath, Kathmandu, Nepal

PO Box 133, Jyoti Bhawan 1911, Kantipath, Kathmandu, Nepal Phone: 01 4225377, 4104540, 4248949 Fax: 01 4212415, Finance: 01 4261770

Toll Free No.: NTC: 16600122033, Ncell: 9801571023
Email: customercare@ngmhero.com, www.ngmhero.com

f www.facebook.com/ngmheromotocorp

It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Accessories and features shown may not be a part of the standard fitment. Always wear a helmet while riding a two wheeler. Warrants valid for a period of 5 vesser of 50,000 kms from the date of ourstands, whichever is earlier Vist wow, becomes consortions.





RIDE WITH EASE



MOBILE CHARGING SOCKET

FLAUNT YOUR STYLE



STUNNING METER CONSOLE



PLAY IT SAFE



INTEGRATED BRAKING & TUBELESS TYRES