



— INTRODUCING —

Xtreme
200*+*

FEAR
NOTHING



SPECIFICATION^
XTREME 200R
ENGINE

Engine Type	Air Cooled, 4 Stroke 2 Valve Single Cylinder OHC
Bore	66.5 mm
Stroke	57.5 mm
Displacement	199.6 cc
Compression Ratio	10:01
Max Power	13.5kW/18.4 PS @ 8000 rpm
Max Torque	17.1 Nm @ 6500 rpm
Fuel System	CV Carburetor (Venturi dia.32)
Starting	Self & Kick
Ignition	Digital DC CDI Ignition System
Air Filter	Viscous Type

TRANSMISSION & CHASSIS

Clutch	Multi Plate Wet Clutch
Gearbox	5 speed Constant Mesh
Frame Type	Diamond Type

SUSPENSION

Front	Telescopic Hydraulic Type (37mm dia) with Antifriction Bush
Rear	7 Step Adjustable Mono-Shock Suspension

BRAKES

Front Brake Type	276 mm disc
Antilock Braking System (ABS)	Single Channel
Rear Brake Type	220 mm Disc

WHEELS & TYRES

Front Tyre Size	100/80-17" - Tubeless
Rear Tyre Size	130/70-R17"-Tubeless

ELECTRICALS

Battery (V-Ah)	12 V - 4 Ah (Maintenance Free Battery)
----------------	--

DIMENSIONS

Length x Width x Height (mm)	2062 x 778 x 1072
Wheelbase	1338 mm
Seat/Saddle Height	795 mm
Ground Clearance	165 mm

WEIGHT

Kerb Weight	148kg
Fuel Tank Capacity	12.5 L

ATTRACTIVE COLOURS

PANTHER BLACK WITH FORCE SILVER

TECHNO BLUE

HEAVY GREY WITH ORANGE


BLACK WITH SPORT RED

SPORT RED


INTRODUCING



Authorized Outlet:



Nepal General Marketing Pvt. Ltd.
 PO Box 133, Jyoti Bhawan 1911, Kantipath, Kathmandu, Nepal
 Phone: 01 4225377, 4104540, 4248949
 Fax: 01 4212415, Finance: 01 4261770
 Toll Free No.: NTC: 16800122033, Ncell: 9801571023
 Email: customercare@ngmhero.com, www.ngmhero.com

 www.facebook.com/ngmheromotocorp

It is our endeavour to constantly improve our product. This could lead to changes in product specifications without notice. Accessories and features shown may not be part of the standard fitment. Always wear a helmet while riding a two-wheeler. For further information, contact the nearest Hero MotoCorp's authorized outlet(s) or visit website www.heromotocorp.com.